

We're here for life

Dual, Variable-Focused 24" LED Surgical Light Fixture Aurora Four

LFSAUA55, LFSAUA5TV5, LFSAUA55TV



Technical Data

Fixture Weight: 198 kg Moment Load: 1799 N·m

Minimum Ceiling Height: 2875mm Maximum Ceiling Height: 3346mm

Electrical: 100-240VAC, 148-240VA, 50/60 Hz, 1 phase Max Intensity at 1 meter (lux): @4100K = 320,000

@4500K = 281,000

Central Illuminance at 1 meter (lux): @4100K = 160,000

@4500K = 140,500

CRI: @4100K = 95 @4500K = 96

Color Temperature: @4100K @4500K

Total Irradiance (watts/m²): @4100K = 532.3

@4500K = 475.9

R9: @4100K = 91 @4500K = 95

Architectural Specification

The Aurora Four surgical lighting system consists of a ceiling mounted radial arm system with a Flat Screen monitor mount and two 24" (610mm) diameter lightheads. Flat Screen monitor mount arm provides 340° rotation at the ceiling mount with adjustable stops. Monitor mount provides 540° of rotation, 150° of tilt and will accommodate up to a 20 pound (9 kg) flat screen monitor. Continuous 360° rotation is provided at all lighthead rotation points.

Standard lightheads are equipped with a sterilisable center handle that allows surgeon control of lighthead positioning, focus and intensity. A focus knob and positioning handles are provided on the side of the lighthead for non-sterile control.

Each 24" (610mm) lighthead contains 5 focusable LED pods. Each focusable pod contains 7 individual LEDs with VSRD reflector technology. Each lighthead also contains 12 fixed focus center mounted LEDs. Total system output is 320,000 lux at a color temperature of 4,100K. LED life expectancy is 40,000 hours.

SKYTRON Aurora Four series, model LFSAUA55, LFSAUA5TV5 or LFSAUA55TV. Flat screen monitors provided separately.




We're here for life

Dual, Variable-Focused 24" LED Surgical Light Fixture Aurora Four

LFSAUA55, LFSAUA5TV5, LFSAUA55TV

Product Elevation View



Mounting

Wall Control **Typical Mounting Structure** - Required, Priced Separately -- Provided by Others -11-3/4 6 Flange Adaptor 7-7/8" (By Others) 3" X 3" Angle Sway Bracing (4) 7/8" ROD 10' 13-7/8" Finished Ceiling 1-1/8"_ (28mm) 4-16-1/2" Dia. Access Hole → 20-1/2" Dia. Ceiling Cover. (Not to Scale) (SKYTRON Supplied) BACK VIEW

Refer to Installation Instructions for specific mounting structure guidelines, wiring and wall control installation details.

AROUT HIPAC

We are an Australian healthcare company that guarantees to stand behind all our medical products, both manufactured and imported, because we're here for the life of our products and clients.

PO Box 797, 36 Long St. Goulburn NSW 2580, Australia P. +61 2 4823 0000 E. info@hipac.com.au

SYDNEY | MELBOURNE | BRISBANE | ADELAIDE | PERTH

